



## Ful Flo Shutter Screen

### Open Area for Stainless, HSLA, and Copper-Bearing Steels

casing diameter (in.)	6-5/8	8-5/8	10-3/4	12-3/4	14-1/2	16-5/8	18-5/8	20-5/8	22-1/2	24-1/2
casing diameter (mm)	168	219	273	324	368	422	473	524	572	622
holes / circle	6	8	8	10	10	12	14	16	16	16
holes / ft	72	96	96	120	120	144	168	192	192	192
holes / meter	236	315	315	394	394	472	551	630	630	630
slot size										
1/16" <small>(Square inches per lineal foot)</small>	7.3	9.8	15.8	19.7	19.7	23.6	27.6	31.5	31.5	31.5
1.59 mm <small>(Square centimeters per lineal meter)</small>	155	206	333	417	417	500	583	667	667	667
3/32"	11.0	14.6	23.6	29.5	29.5	35.4	41.3	47.2	47.2	47.2
2.38 mm	232	310	500	625	625	750	875	1000	1000	1000
1/8"	14.6	19.5	31.5	39.4	39.4	47.2	55.1	63.0	63.0	63.0
3.18 mm	310	413	667	834	834	1000	1167	1334	1334	1334
5/32"	18.3	24.4	39.4	49.2	49.2	59.1	68.9	78.8	78.8	78.8
3.97 mm	387	516	834	1042	1042	1250	1459	1667	1667	1667
3/16"	21.9	29.2	47.2	59.1	59.1	70.9	82.7	94.5	94.5	94.5
4.76 mm	464	619	1000	1250	1250	1500	1750	2001	2001	2001
1/4"	29.2	39.0	63.0	78.8	78.8	94.5	110.2	126.0	126.0	126.0
6.35 mm	619	826	1334	1667	1667	2001	2334	2667	2667	2667

