



## Super Flo Shutter Screen

*Open Area for Stainless, HSLA, and Copper-Bearing Steels*

casing diameter (in.)	6-5/8	8-5/8	10-3/4	12-3/4	14-1/2	16-5/8	18-5/8	20-5/8	22-1/2	24-1/2
casing diameter (mm)	168	219	273	324	368	422	473	524	572	622
holes / circle	8	10	12	14	16	18	20	22	24	26
holes / ft	192	240	288	336	384	432	480	528	576	624
holes / meter	630	787	945	1102	1260	1417	1575	1732	1890	2047
slot size										
1/16" (Square inches per lineal foot)	21.0	26.2	31.5	36.8	42.0	47.2	52.5	57.8	63.0	68.2
1.59 mm (Square centimeters per lineal meter)	446	557	669	780	891	1003	1114	1226	1337	1449
3/32"	31.2	39.1	46.9	54.7	62.5	70.3	78.1	85.9	93.7	101.6
2.38 mm	667	834	1001	1168	1334	1501	1668	1835	2002	2168
1/8"	42.0	52.5	63.0	73.5	84.0	94.5	105.0	115.5	126.0	136.5
3.18 mm	891	1114	1337	1560	1783	2006	2229	2451	2674	2897
5/32"	52.4	65.5	78.6	91.7	104.8	117.9	131.0	144.1	157.2	170.4
3.97 mm	1113	1391	1669	1948	2226	2504	2782	3060	3339	3617
3/16"	63.2	79.0	94.8	110.5	126.3	142.1	157.9	173.7	189.5	205.3
4.76 mm	1334	1668	2002	2335	2669	3002	3336	3670	4003	4337

